



Farve: ■ lysegrå

Elektriske data

Mærkninger iht. IEC/EN

Nominal spænding (III/3)	800 V
Mærkepulsspænding (III/3)	8 kV
Mærkestrøm	25 A

Fysiske data

Bredde	10,9 mm / 0.429 tommer
Højde	4,1 mm / 0.161 tommer
Dybde	18,5 mm / 0.728 tommer
Laske tildeling	1-4

Materialedata

Note (materiel data)

[Oplysninger om materialespecifikationer kan findes her/a](#)

Farve	lysegrå
Brand last	0.012 MJ
Vægt	1.1 g

Kommercielle data

PU (SPU)	25 Stykke
Emballage type	Pose
Oprindelsesland	DE
GTIN	4066966320220
Told tarifnummer	85366990990

Product Classification

UNSPSC	39121421
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Produktets miljøoverholdelse

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 2002-424



CAD/CAE-Data


CAD data

2D/3D Models
2002-424




Installeringsbemærkninger:

Laskning



The 1-to-3 adjacent jumper for continuous commoning enables every other terminal block to be commoned. For example, positive and negative potentials can be accommodated alongside each other.

Laskning



By combining a 1-to-2 continuous jumper with a 1-to-3 adjacent jumper, various commoning applications can be performed in just one jumper slot.